BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 23 December 2004 (23.12.2004)

PCT

(10) International Publication Number WO 2004/112019 A1

(51) International Patent Classification7: 27/30

G11B 20/10,

(21) International Application Number:

PCT/IB2004/001969

(22) International Filing Date:

8 June 2004 (08.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 03300031.6

17 June 2003 (17.06.2003)

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): IMMINK, Albert [NL/NL]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR). COENE, Willem [BE/NL]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR). BERGMANS, Johannes [NL/NL]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR). RIANI, Jamai [MA/NL]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR).
- (74) Agent: ROCHE, Denis; Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EB, EG, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA,

[Continued on next page]

(54) Title: CHANNEL SYNCHRONIZATION FOR TWO-DIMENSIONAL OPTICAL RECORDING



two dimensional optical read-out system. Said synchronization method computes a step of comprises a step of iterating the of adjacent channels for determining a relative phase delay between said adjacent channels. It finally comprises a step of compensating cross-correlation step for the different pair of adjacent channels of the set of data channels. It finally comprises a step of compensating for the relative phase delays thus obtained in order to align the signals from adjacent channels with each other. The present invention is based on, for example, the use of the optical cross talk existing between adjacent channels in a cross correlator that is able to determine the relative phase between two adjacent channels.